



HDS 17/20 De Tr1

Self-sufficient and mobile: the HDS 17/20 hot water high-pressure cleaner works without power source at pressures of 200 bar. The highly-efficient HDS Trailer is suitable for the municipal sector, industry and construction.









1 Simple operation

2 Service-friendly

TECHNICAL DATA AND EQUIPMENT.





HDS 17/20 De Tr1

Technical data		
Order Number		1.524-952.2
Engine manufacturer		Yanmar
Fuel		Diesel
Power rating	kW / hp	19 / 26 / 19 / 26
Flow rate	l/h	900-1700
Pressure	bar / MPa	60-200 / 6-20
	kg/h	11,8
Weight	kg	950
Dimensions (L x W x H)	mm	3646 × 1747 × 1735

Equipment		
Trigger gun		EASY!Force Advanced
High-pressure hose	m	30
Spray lance	mm	1050
Power nozzle		
Servo Control		-

■ Included in delivery.













								Π
		Order Number	ID	Max. working pressure	Length	Price	Description	
Standard with unions on both sides								
High-pressure hose, 15 m DN 10, 220 bar, extension	1	6.110-042.0	ID 10	220 bar	15 m		15 m high-pressure hose M 22 x 1.5) with kink protection and threaded couplings at both ends. Further data: DN 10/155°C/220 bar.	A
High-pressure hose, 20 m DN 10, 220 bar, extension	2	6.110-043.0	ID 10	220 bar	20 m		with union on both sides, M 22 x 1.5 with anti-kink protection. NW 10/155°C/220 bar	•
High-pressure hose, 25 m DN 10, extension, not rotatable	3	6.110-044.0	ID 10	220 bar	25 m			A
Hose assembly premium DN12 21MPa 15m	4	6.110-059.0	ID 12	250 bar	15 m		High-pressure hose for water volumes greater than 1,800 l / h. With union on both sides. 2x M 22 x 1.5 with anti-kink	A
Hose assembly premium DN12 21MPa 40m	5	6.110-060.0	ID 12	250 bar	40 m		protection.	A
Longlife food industry version with	union	s on both sides						
High pressure hose food DN 8 / 10 m	6	6.110-053.0	ID 8	400 bar	10 m		Longlife HP hose for use in the food industry. Außende- cke## animal-grease-resistant, non-colour-bleeding materi- al. With rotary coupling, 2 x M 22 x 1,5	•

[☐] Available accessories. ▲ Extension hose.





		Order Number			Price	Description	
Y distributor							
Y distributor	1	4.111-024.0					









		Order Number	· Flow rate	Nozzle size	Diame- ter	Price	Description	
Hard Surface Cleaner FR 50		<u> </u>	'					
FR 50 surface cleaner	1	2.111-023.0			500 mm		Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas.With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system.	
Machine-specific nozzle kit for FR								
Nozzle pack for hard surface cleaners (machine-specific) 1300 - 1,800 l/h	2	2.640-781.0	1300-1800 l/h				Machine-specific nozzle kit Kärcher power nozzle for hard surface cleaners	
Machine-specific nozzle kits for FR	V							
Nozzle 100	3	2.643-769.0		100				
Surface Cleaner FR 50 Me								
	4	2.111-024.0						

[☐] Available accessories. ▲ Extension hose.





























		Order Number			Price	Description
Nozzle union						
Protection part TR only for replacement	1	4.112-011.0				
Coupling parts						
	2	6.987-705.0				
Rotary coupling		,				,
Rotary coupling	3	4.111-021.0				Kärcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector M 22 x 1.5 m. With grip protection.
Coupling						,
Coupler -2xM22x1,5	4	4.111-037.0				Brass double connector for connecting and extending high- pressure hoses. With rubber protection. Connector: 2x M 22 x 1.5 m.
Connector						,
Nozzle connector/screw connector	5	4.111-022.0				Nozzle connector/screw connector for connecting high- pressure nozzles and accessories to the high-pressure trig- ger gun (with nozzle connector). Connectors: 1x M 22 x 1.5 and 1x M 18 x 1.5.
	6	4.111-038.0				
Adapter EASY!Lock						
Adapter 1 M22AG-TR22AG	7	4.111-029.0				
Adapter 2 M22IG-TR22AG	8	4.111-030.0				
Adapter 3 M22IG-TR22AG	9	4.111-031.0				
Adapter M22 - Swivel	10	4.111-032.0				M22 x 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection.
Adapter 5 TR22IG-M22AG	11	4.111-033.0				
Adapter 6 TR22IG-M22AG	12	4.111-034.0				
Adapter 7 M18IG-TR20AG	13	4.111-035.0				
Adapter 8 TR20IG-M18AG	1./	4.111-036.0]

 $[\]hfill \square$ Available accessories. $\hfill \blacktriangle$ Extension hose.











		Order Number	Elow rate		Price	Description	
		Order Norriber	riow rate		PIICE	Description .	_
Trigger guns						,	
Extended easy press trigger gun	1	4.118-005.0				Extended easy press high-pressure trigger gun for high- pressure hoses with rotating connector.	
Servo Control							
Servo control	2	4.118-009.0	1100 l/h				
Quick connect							
Quick-fitting pipe union coupler trapezo	3	2.115-000.0					
Quick-fitting pipe union plug nipp- le tra	4	2.115-001.0					

[☐] Available accessories. ▲ Extension hose.





	Order Number	Nozzle size				Price	Description	
1	2.113-052.0	100					Fan jet nozzle for stubborn dirt and stains.	
2	2.113-016.0	90						
3	2.113-069.0	90						
	2		2 2.113-016.0 90	1 2.113-052.0 100 2 2.113-016.0 90	1 2.113-052.0 100 2 2.113-016.0 90	1 2.113-052.0 100	1 2.113-052.0 100	1 2.113-052.0 100 Fan jet nozzle for stubborn dirt and stains. 2 2.113-016.0 90

[☐] Available accessories. ▲ Extension hose.







		Order Number	Nozzle size		Price	Description
Wet blasting attachment (without r	nozzle)					
Wet blasting attachment with flow control (without nozzles)	1	4.115-000.0				Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.
Wet blasting attachment without flow control (nozzles not included)	2	4.115-006.0				Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.
Nozzle pack for wet blasting attach	ment					
Nozzle pack for wet blasting at- tachment	3	2.637-909.0	90			Consisting of wet-blasting nozzle and nozzle insert, only for use with wet-blasting attachment 4762-010/-022
Boron carbide nozzle						
Boron carbide nozzle, for machines as of 1000 l/h	4	6.415-083.0	8 mm			In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.

[☐] Available accessories. ▲ Extension hose.







								Т
		Order Number	Max. working pressure	Nozzle size	Diame- ter	Price	Description	
Pipe cleaning hose, ID 6								
Hose assembly TR pipe cleaning DN6 max.2	1	6.110-046.0	250 bar					
Pipe cleaning hose, DN 6, 20 m, 220 bar	2	6.110-008.0	250 bar				20 m flexible high-pressure hose (DN 6) for cleaning pipes up to 220 bar (threaded connection for R 1/8 nozzle).	
Hose assembly TR pipe cleaning DN6 max.2	3	6.110-047.0	250 bar					
Pipe cleaning nozzle								
Nozzle pipe cleaning size 100	4	5.763-088.0		100	24 mm		Pipe cleaning nozzle with 24 mm diameter. With 4 nozzles tilted back at a 30° angle.	

[☐] Available accessories. ▲ Extension hose.





		Order Number	Max. working pressure	Nozzle size		Price	Description
Dirt blaster, large							
Dirt blaster - non-changeover	1	4.114-043.0	300 bar	90			Dirt blaster – rotating pencil jet – 10x cleaning power. Ceramic nozzle and bearing ring for long service life. Max. 300 bar/30 MPa, 85 °C

[☐] Available accessories. ▲ Extension hose.













						I	
	O., d N	= 1				B	Bi-st
	Order Number	Flow rate				Price	Description
1	2.112-017.0						
2	6.414-954.0						
3	2.112-008.0						High-pressure foam system with double lance (foam nozzle
							and high-pressure jet for rinsing). For use with mobile and
							stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.
					<u> </u>	l	realing or distriction.
4	2.112-011.0						HP foam system for use with. HD/HDS units for cleaning and
							disinfecting. Foam nozzle for connection to lance and HP
							chemical injector with precision 0-5% metering valve. The
							machine specific nozzle kit has to be ordered separately.
5	2.111-020.0	1000-1300 l/h					Nozzle kit 110 contains Kärcher power nozzles and nozzle
							inserts. For Inn/Easy-Foam set 1000-1300 l/h. For optimal
							foam system performance.
6	2 1 1 2 0 1 2 0			l		l	Foaming agent kit. The foam nozzle is ideal for use in sani-
Ь	2.112-013.0						tary areas and the food industry and wherever long applica-
							tion times are necessary.
	3	1 2.112-017.0 2 6.414-954.0 3 2.112-008.0 4 2.112-011.0 5 2.111-020.0	2 6.414-954.0 3 2.112-008.0 4 2.112-011.0 5 2.111-020.0 1000-1300 l/h	1 2.112-017.0 2 6.414-954.0 3 2.112-008.0 4 2.112-011.0 5 2.111-020.0 1000-1300 l/h	1 2.112-017.0 2 6.414-954.0 3 2.112-008.0 4 2.112-011.0 5 2.111-020.0 1000-1300 l/h	1 2.112-017.0 2 6.414-954.0 3 2.112-008.0 4 2.112-011.0 5 2.111-020.0 1000-1300 l/h	1 2.112-017.0 2 6.414-954.0 3 2.112-008.0 4 2.112-011.0 5 2.111-020.0 1000-1300 l/h

[☐] Available accessories. ▲ Extension hose.

















		Order Number	Length		Price	Description	
Automatic, self-winding hose reels				 I.			
Add-on kit hose reel plastics	1	6.392-074.0	20 m			Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.	
Add-on kit hose reel	2	6.392-083.0	20 m			Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.	
Hose reel, automatic, 20 m, painted	3	6.392-106.0	20 m			Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.	
	4	6.392-105.0	20 m				
Hose reel, automatic, 20 m, stain- less steel	5	6.392-076.0	20 m			Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	
ABS hose reel stainless steel	6	6.392-122.0	20 m			High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrossion-resistant, watertight capsuled sprong drive. Connection for HP hoses with nipple.	1 1
Swivel holder	7	2.639-931.0				Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.	. 🗆
ABS wall fastening stainless steel	8	2.641-867.0				Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.	

[☐] Available accessories. ▲ Extension hose.





		1	1	1	1				_
		Order Number	Max. working pressure	Length			Price	Description	
Rotating spray lances		I	ı	ı					
Lance 250 mm, non-rotatable	1	4.112-027.0	300 bar	250 mm					
550 mm lance, non-rotatable	2	4.112-024.0	300 bar	400 mm					
Rotatable lance, 600 mm, ergonomic	3	4.112-007.0	300 bar	600 mm				600 mm stainless steel lance (manual coupling) with ergono mic handle for ease of use and protection. Rotatable 360° under pressure.	
Lance 850 mm, rotatable, ergonomic	4	4.112-006.0	300 bar	840 mm				850 mm stainless steel lance (manual coupling) with ergono mic handle for ease of use and protection. Rotatable 360° under pressure.	
1050 mm lance, rotatable, ergonomic	5	4.112-000.0	300 bar	1050 mm				1050 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360' under pressure.	, 0
Lance 1550 mm, rotatable, ergonomic	6	4.112-018.0	300 bar	1550 mm				1550 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360' under pressure.	. 0
Lance 2050 mm, rotatable, ergonomic	7	4.112-021.0	300 bar	2050 mm				2050 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360' under pressure.	, 🗆
Double lance									
Double lance 960 mm	8	6.394-665.0	310 bar	960 mm				960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).	
Angular spray lance									
WC and gutter lance	9	4.112-029.0						Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.	
Flexible spray lance									
Flexible lance 1050 mm	10	4.112-035.0	210 bar	1050 mm				1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.	
Telescopic spray lance	l	l	l	l =	1			I	
Telescopic jet pipe	11		225 bar	5400 mm					
Restraint belt for telescopic jet pipe	12	6.373-987.0						Convenient strap for relief when working with the telesco- pic spray lance (6.394-690). The burden is optimally distri- buted on the body and longer periods of use are possible.	
Gutter cleaner		1				,			
Gutter cleaning lance	13	2.112-015.0						The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.	
Undercarriage spray lance									
Underbody lance	14	4.112-032.0		700 mm				Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	
Additional handle		ı	1	1					
	15	4.321-380.0							

[☐] Available accessories. ▲ Extension hose.









		Ouden Nomber	Flancemata		Duise	Bassintian	
		Order Number	Flow rate		Price	Description	
Push-on washing brush							
Push-on wash brush, M 18 x 1.5	1	4.113-001.0				Push-on wash brush for universal use. Simply push on to	\neg
						lance. Connector: M 18 x 1.6.	Ц
Rotating washing brush							
	2	4.113-002.0	800-1300 l/h				
	3	4.113-005.0	800-1300 l/h				

[☐] Available accessories. ▲ Extension hose.









		Order Number	Length	Diameter		Price	Description
Suction filter							
Water filter	1	6.414-956.0					
Suction filter with check valve	2	4.730-012.0					Brass suction filter suitable for ponds, storage tanks, etc. With check valve.
Fine-mesh water filter							
Fine-mesh water filter with adapter	3	4.730-102.0					Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1".

[☐] Available accessories. ▲ Extension hose.